


## → A2 NOX Series



### NOX

- Topless direct gate small residue on the part
- One exit options for shear sensitive materials



NOX

(mm)

Size	Size 05	Size 07
L	45~125	45~165
Feed $\phi$	5	7
Gate $\phi$	0.6~2	0.8~3

Shot Weight(g)		
Low-viscosity	200	400
Medium-viscosity	100	260
High-viscosity	20	50

## → A2 NOX Dimension

(mm)

		A2 NOX													
		05						07							
Nozzle	Size	45	55	65	85	105	125	45	65	85	105	125	145	165	
	L	45	55	65	85	105	125	45	65	85	105	125	145	165	
	d1	5						7							
	d3	C30,T30						T36,T40,T50							
	d4	29						35							
	d5	20						24							
	d6	23						27							
	d7	18						24.5							
Mould	L1	45.11	55.13	65.15	85.18	105.22	125.26	45.12	65.15	85.19	105.23	125.27	145.31	165.34	
	L2a	2						2.5							
	L3	8.5						8.5							
	D1a	10						12							
	D2	8						9							
	D3	2≥0.6						3≥0.8							
	D4	20						26.5							
	D5	5						7							
	D6	23						27							
	D7	C30,T30						T36,T40,T50							
	D8	23						27							

d3:C=Ceramic T=Titanium